


SBX-LSE (SECURITY LOCK BOX)

## NOTES:

- RISER DIAGRAM ABOVE IS DIAGRAMMATIC AND IS SHOWN TO PROVIDE A GENERAL OVERVIEW OF MAJOR SYSTEM COMPONENTS AND INTERCONNECTIONS. THIS DIAGRAM IS NOT TO BE USED FOR FIELD INSTALLATION PURPOSES.
- 2. ALL WIRING SHALL BE IN CONDUIT, 1" MINIMUM. ALL WIRING SHALL BE PROVIDED ACCORDING TO THE MANUFACTURER'S INSTRUCTIONS.
- PROVIDE ALL ANCILLARY COMPONENTS, HARDWARE, POWER CONNECTIONS, AND WIRING AS REQUIRED FOR COMPLETE AND OPERATING DOOR INTERCOM SYSTEM.
- 4. SYSTEM SHALL BE AS MANUFACTURED BY AIPHONE:
  - A. HANDSFREE MASTER STATION: MODEL JF-2MED.
  - B. DOOR INTERCOM STATION: MODEL JF-DVF.
  - C. SELECTIVE DOOR RELEASE ADAPTOR: MODEL RY-3DL.
  - D. POWER SUPPLY: MODEL PS-1820UL.
  - E. BACKBOX: MODEL SBX-DVF SHALL BE INSTALLED WHEN BRICK MASONRY WALL IS INDICATED.
  - F. SECURITY LOCK BOX: MODEL SBX-LSE SHALL BE INSTALLED FOR AFTER HOURS LOCK DOWN.
- 5. CONTACT AIPHONE COMMUNICATIONS (800) 692-0200 FOR FURTHER INFORMATION.



| DESCRIBED | CPS | CPS